


19343 KDEM-1P LCD

Electricity meter, 1P, In 45A













The KDEM-1P LCD is a device designed for monitoring electricpower consumption in three-phase installations. It can be used in commercial and industrial applications. It measures and displays active power consumption (kWh). The meter uses the directmeasurement method 5A (100A). The KDEM-1P LCD is a meter compliant with the MID directive (accuracy-class B). It is equipped with additional pulsed output, which affords the capability to measure electric-power consumption remotely. The meter can be installed on DIN rails (TH35). The meter is pre-sealed, and it is also possible to seal the covers of the clamps for supply lines.

GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35 Place of application: Indoors

Norm: PN-EN 60715

Supply-voltage tolerance: +/- 10%

Measuring diode: yes Length [mm]: 17.5 Width [mm]: 17.5 Height [mm]: 113

TECHNICAL DATA:

Rated voltage [V]: 230 AC Rated frequency [Hz]: 50

Ambient temperature range to which the product can be

exposed: -10÷35

Connection type: Terminal block

Range of sections of wires used [mm²]: 2,5-6 Measuring diode - pulse weight [p/KWh]: 2000

Number of modules: 1 Maximum current [A]: 45

IP class: 20

Counter measuring range: 99999,99

Prąd bazowy [A]: 0,25-5 Minimum current [A]: 0.02 Meter constant [Wh/imp]: 0.5

Pulse output: S0+S0- | <27V DC | <27mA Internal power consumption [VA]: max ≤4

Measurement precision class: B

Date of issue: 05.06.2024, 17:49

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

