

KMB6

Overcurrent circuit breaker, 3P



[Hz]

50

B

3P

3

IP

20

1÷25

5÷40

TH 35

Ui [V]

500

CE

EAC

VDE

UK
CA

KMB6-B16/3

	[V]		In [A]
KMB6-B16/3	23149 230/400 AC	3	16
KMB6-B20/3	23152 230/400 AC	3	20
KMB6-B25/3	23153 230/400 AC	3	25
KMB6-B32/3	23159 230/400 AC	3	32
KMB6-B10/3	23164 230/400 AC	3	10
KMB6-B40/3	23168 230/400 AC	3	40
KMB6-B63/3	23170 230/400 AC	3	63
KMB6-B6/3	23171 230/400 AC	3	6
KMB6-B50/3	23172 230/400 AC	3	50

Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

KMB6

Overcurrent circuit breaker, 3P



KMB6-B16/3



KMB6-B20/3



KMB6-B25/3



KMB6-B32/3



KMB6-B10/3



KMB6-B40/3




KMB6-B63/3




KMB6-B6/3




KMB6-B50/3




KMB6-B16/3



KMB6-B20/3




KMB6-B25/3




KMB6-B32/3

KMB6


Overcurrent circuit breaker, 3P




KMB6-B10/3




KMB6-B40/3



KMB6-B63/3



KMB6-B6/3



KMB6-B50/3