

# KMB6

Miniature circuit breaker, 2P



[Hz]

50

B

2P

2

IP

20

[mm<sup>2</sup>]  
1÷25

°C  
5÷40

TH 35

Ui [V]

500

CE

EAC

VDE

UK  
CA

KMB6-B6/2

	<div>[V]</div>	<div></div>	<div>In [A]</div>
KMB6-B6/2	<b>32574</b>	230 AC	2 6
KMB6-B10/2	<b>32575</b>	230 AC	2 10
KMB6-B16/2	<b>32576</b>	230 AC	2 16
KMB6-B20/2	<b>32577</b>	230 AC	2 20
KMB6-B25/2	<b>32578</b>	230 AC	2 25
KMB6-B32/2	<b>32579</b>	230 AC	2 32
KMB6-B40/2	<b>32580</b>	230 AC	2 40
KMB6-B50/2	<b>32581</b>	230 AC	2 50
KMB6-B63/2	<b>32582</b>	230 AC	2 63

Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

KMB6

Miniature circuit breaker, 2P



KMB6-B6/2



KMB6-B10/2



KMB6-B16/2



KMB6-B20/2



KMB6-B25/2



KMB6-B32/2




KMB6-B40/2




KMB6-B50/2




KMB6-B63/2




KMB6-B6/2



KMB6-B10/2




KMB6-B16/2




KMB6-B20/2

## KMB6


Miniature circuit breaker, 2P




KMB6-B25/2




KMB6-B32/2



KMB6-B40/2



KMB6-B50/2



KMB6-B63/2