

KSPD

Surge protector



[Hz]  
50

IP  
20

-5÷40

5÷95

TH 35

CE

EAC

UK  
CA



KSPD-T2 275/40 1P

		<div><div>[V]</div><div></div></div>	Protection type		
KSPD-T2 275/40 1P	36310	230 AC	1	T2 (C)	
KSPD-T2 275/120 3P	36311	230 AC	3	T2 (C)	
KSPD-T2 275/160 3P+N	36312	230 AC	4	T2 (C)	
KSPD-T1T2 275/50 1P	36313	230 AC	1	T1+T2 (B+C)	
KSPD-T1T2 275/100 1PN	36314	230 AC	2	T1+T2 (B+C)	
KSPD-T1T2 275/150 3P	36315	230 AC	3	T1+T2 (B+C)	
KSPD-T1T2 275/200 3PN	36316	230 AC	4	T1+T2 (B+C)	
KSPD-TT 275/160 3P+N	36317	230 AC	4	T2 (C)	

The surge arrester, class 1+2 (T1+T2/B+C), is used to protect LV power supply installations from the effects of surges generated during lightning discharges as well as induced or switching surges / intended for installation in TN/TT networks Complies with standard: EN61643-1, EN61643-11. Surge arresters (KSPD), type KSD-T1+T2, are manufactured in accordance with EN61643-1 and EN61643-11 standards. Type 1+2 surge arresters are engineered to protect low-voltage installations against partial, direct and indirect lightning discharges. The arresters provide protection inside 0A-I zone in accordance with standard EN62305.

KSPD

Surge protector



KSPD-T2 275/40 1P



KSPD-T2 275/120 3P



KSPD-T2 275/160 3P+N



KSPD-T1T2 275/50 1P



KSPD-T1T2 275/100 1PN




KSPD-T1T2 275/150 3P




KSPD-T1T2 275/200 3PN




KSPD-TT 275/160 3P+N




KSPD-T2 275/40 1P



KSPD-T2 275/120 3P




KSPD-T2 275/160 3P+N




KSPD-T1T2 275/50 1P

## KSPD


### Surge protector




KSPD-TIT2 275/100 1PN



KSPD-TIT2 275/150 3P



KSPD-TIT2 275/200 3PN



KSPD-TT 275/160 3P+N