

KMB6

Wyłącznik nadmiarowo-prądowy, 3P



[Hz] 50	B	3P	3	IP 20	(mm²) 1÷25	t°C -5÷40
TH 35	Ui [V] 500	CE	ERC	VDE	UC CPA	

KMB6-B16/3

	[V]		In [A]
KMB6-B16/3	23149	230/400 AC	3 16
KMB6-B20/3	23152	230/400 AC	3 20
KMB6-B25/3	23153	230/400 AC	3 25
KMB6-B32/3	23159	230/400 AC	3 32
KMB6-B10/3	23164	230/400 AC	3 10
KMB6-B40/3	23168	230/400 AC	3 40
KMB6-B63/3	23170	230/400 AC	3 63
KMB6-B6/3	23171	230/400 AC	3 6
KMB6-B50/3	23172	230/400 AC	3 50

Wyłącznik z zabezpieczeniem nadmiarowo-prądowym służy do ochrony przewodów przed przeciążeniami i zwarciami w instalacjach i urządzeniach.

- Certyfikat VDE: Numer 40051584

KMB6

Wyłącznik nadmiarowo-prądowy, 3P



KMB6-B16/3



KMB6-B20/3



KMB6-B25/3



KMB6-B32/3



KMB6-B10/3



KMB6-B40/3



KMB6-B63/3




KMB6-B6/3




KMB6-B50/3

KMB6


Wyłącznik nadmiarowo-prądowy, 3P




KMB6-B16/3




KMB6-B20/3




KMB6-B25/3




KMB6-B32/3




KMB6-B10/3




KMB6-B40/3



KMB6-B63/3



KMB6-B6/3



KMB6-B50/3