

KMB6

Wyłącznik nadmiarowo-prądowy, 4P



[Hz]
50

B

4P

4

IP
20

1÷25

-5÷40

TH 35

Ui [V]
500

CE

EAC

VDE

CNK
PA



KMB6-B6/4

		[V]		In [A]
KMB6-B6/4	32592	400 AC	4	6
KMB6-B10/4	32593	400 AC	4	10
KMB6-B16/4	32594	400 AC	4	16
KMB6-B20/4	32595	400 AC	4	20
KMB6-B25/4	32596	400 AC	4	25
KMB6-B32/4	32597	400 AC	4	32
KMB6-B40/4	32598	400 AC	4	40
KMB6-B50/4	32599	400 AC	4	50
KMB6-B63/4	32600	400 AC	4	63

Wyłącznik z zabezpieczeniem nadmiarowo-prądowym służy do ochrony przewodów przed przeciążeniami i zwarciami w instalacjach i urządzeniach.

- Certyfikat VDE: Numer 40051584

KMB6

Wyłącznik nadmiarowo-prądowy, 4P



KMB6-B6/4



KMB6-B10/4



KMB6-B16/4



KMB6-B20/4



KMB6-B25/4



KMB6-B32/4



KMB6-B40/4




KMB6-B50/4




KMB6-B63/4

KMB6


Wyłącznik nadmiarowo-prądowy, 4P




KMB6-B6/4




KMB6-B10/4




KMB6-B16/4




KMB6-B20/4




KMB6-B25/4




KMB6-B32/4



KMB6-B40/4



KMB6-B50/4



KMB6-B63/4