



23149 KMB6-B16/3

Overcurrent circuit breaker, 3P

5905339231499

















Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

GENERAL DATA:

Colour: white

Place of assembly: rail TH35

Norm: PN-EN 60898-1

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 16 Rated frequency [Hz]: 50

Ambient temperature range to which the product can be

exposed: 5÷40

Range of sections of wires used [mm 2]: $1 \div 25$

Release characteristics: B Energy-limit class: 3 Number of modules: 3

Rated short-circuit current [A]: 6000

IP class: 20

Number of poles: 3

LOGISTIC DATA:

Packaging method: 4


Number of units in the secondary packaging: 4

Number of units in the packaging: 40

Net unit weight [g]: 300 Grammage [g]: 330

Length of a unit pack [cm]: 5.5 Width of a unit pack [cm]: 7.5 Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.2 Width of a cardboard box [cm]: 25 Height of a cardboard box [cm]: 19.5 Length of a cardboard box [cm]: 45 Volume of a cardboard box [m³]: 0.021938







23149 KMB6-B16/3

Overcurrent circuit breaker, 3P

