


23247 KMC-25-31

Modular contactor, 230 VAC control voltage

5905339232472



Contactors are used for automatic activation of electricity receivers. Categories of use AC7a, AC7b.

GENERAL DATA:

Utilisation category: AC-7A, AC-7B

Colour: white

Place of assembly: rail TH35

Place of application: Indoors

Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Rated voltage [V]: 230 AC

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Connection type: Terminal block

Number of n.o./n.c. contacts: 3/1

Number of modules: 2

Rated power AC-7A/400: 15kW

Rated power AC-7B/400: 4kW

Coil-supply voltage [V]: 230V AC 50/60Hz

Rated current I(N) AC-7A/AC-1: 25A

Rated current I(N) AC-7B/AC-1: 8,5A

IP class: 20

LOGISTIC DATA:

Packaging method: 6

Number of units in the secondary packaging: 6

Number of units in the packaging: 60

Net unit weight [g]: 210

Grammage [g]: 230

Length of a unit pack [cm]: 3.5

Width of a unit pack [cm]: 7.5

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.8

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.024346

23247 KMC-25-31

Modular contactor, 230 VAC control voltage