


23628 KDB-F36P

KDB-series distribution board

5905339236289



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

GENERAL DATA:

Colour: white

Door colour: white

Place of assembly: Recessed mount in the wall

Norm: PN-EN 62208

Length [mm]: 426

Width [mm]: 109

Height [mm]: 310

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Number of modules: 2x18P

Temperature resistance [°C]: 650

IK class: 07

IP class: 30

number of rows: 2

Ilość zacisków N/PE: (6+6+6)x2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1696

Grammage [g]: 2174

Gross unit weight [g]: 1970

Length of a unit pack [cm]: 33

Width of a unit pack [cm]: 11.5

Height of a unit pack [cm]: 43.5

23628 KDB-F36P

KDB-series distribution board

Weight of a cardboard box [kg]: 10.87
Width of a cardboard box [cm]: 35.5
Height of a cardboard box [cm]: 46
Length of a cardboard box [cm]: 58.5
Volume of a cardboard box [m³]: 0.095531