


23629 KDB-S36P

KDB-series distribution board

5905339236296



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

GENERAL DATA:

Colour: white

Door colour: white

Place of assembly: wall mounted

Norm: PN-EN 62208

Length [mm]: 410

Width [mm]: 109

Height [mm]: 294

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Number of modules: 2x18P

Temperature resistance [°C]: 650

IK class: 07

IP class: 30

number of rows: 2

Ilość zacisków N/PE: (6+6+6)x2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1644

Grammage [g]: 2096

Gross unit weight [g]: 1910

Length of a unit pack [cm]: 31

Width of a unit pack [cm]: 11.5

Height of a unit pack [cm]: 42.5

23629 KDB-S36P

KDB-series distribution board

Weight of a cardboard box [kg] : 10.48
Width of a cardboard box [cm] : 32
Height of a cardboard box [cm] : 44
Length of a cardboard box [cm] : 58.5
Volume of a cardboard box [m³] : 0.082368