

## 23924 KSD-T1+T2 275/60 M

Surge protector

5905339239242



### GENERAL DATA:

**Place of assembly:** na szynę TH35

**Place of application:** Indoors

**Norm:** PN-EN61643-1

**Number of fields:** 1

### TECHNICAL DATA:

**Rated voltage [V]:** 230 AC

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -5÷40

**Connection type:** Terminal block

**Protection type:** T1+T2 (B+C)

**Number of modules:** 1

**The highest voltage of continuous operation U(c):** 275V

**The highest discharge power I<sub>max</sub>:** 60kA

**Voltage protection level U(p):** ≤1,3kV

**Residual current I(pe):** 30μA

**Impulse-current I<sub>imp</sub> [kA]:** 12.5

**Transitory current-strength increase [kA]:** 30

**Expected short-circuit current I<sub>fi</sub> [A] r.m.s.:** 100

**IP class:** 20

**Relative humidity range:** 5÷95

**Rated discharge current I<sub>n</sub> [kA]:** 30

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 1

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 1

**Net unit weight [g]:** 86

**Grammage [g]:** 106

**Length of a unit pack [cm]:** 10.5

**Width of a unit pack [cm]:** 2.5

**Height of a unit pack [cm]:** 7.5

**Weight of a cardboard box [kg]:** 0.106

**Width of a cardboard box [cm]:** 2.5

**Height of a cardboard box [cm]:** 7.5

**Length of a cardboard box [cm]:** 10.5

**Volume of a cardboard box [m<sup>3</sup>]:** 0.000197