


24093 KCPM-09-24

KCP power contactor

5905339240934







Miniature power contactors are designed to connect AC circuits in AC3 utilisation category. Current range of the offer up to 12A, supply voltage: 24VAC or 230VAC. As a standard, contactors have a 1NO auxiliary contact.

GENERAL DATA:

Utilisation category: AC-3

Colour: white

Place of assembly: rail TH35 Norm: PN-EN 60947-4-1

TECHNICAL DATA:

Rated frequency [Hz]: 50

Connection type: Terminal block

Electric connection frequency AC-3 [number/h]: 1200 Electric connection frequency AC-4 [number/h]: 300 Mechanical connection frequency [number/h]: 3600

Impedancja na biegun [mΩ]: 3

Rated operating power AC-3 220-240V: 2,2kW Rated operating power AC-3 380-400V: 4kW Rated operating power AC-3 660-690V: 4kW

Coil-supply voltage [V]: 24 AC Rated breaking voltage Ue [V]: 400 Conventional thermal current Ith [A]: 20

Tightening force [Nm]: 0,8Nm


IP class: 20 Main contacts: 3 Auxiliary contacts: 1


Rated insulation voltage UI [V]: 690

Rated impulse withstand voltage Uimp [V]: 6000

Rated operational current le [A]: 9

Rated operating current 380V - In AC-3: 9A
Rated operating current 380V - In AC-4: 3,5A
Rated operating current 440V - In AC-1: 20A
Żywotność elektryczna (x10³) AC-3: 1200
Żywotność elektryczna (x10³) AC-4: 200
Żywotność mechaniczna (x10°): 10Nm









24093 KCPM-09-24

KCP power contactor

LOGISTIC DATA:

Packaging method: 100

Number of units in the secondary packaging: 1

Number of units in the packaging: 100

Net unit weight [g]: 176 **Grammage [g]**: 186

Length of a unit pack [cm]: 6 Width of a unit pack [cm]: 5 Height of a unit pack [cm]: 6.5 Weight of a cardboard box [kg]: 18.6 Width of a cardboard box [cm]: 25 Height of a cardboard box [cm]: 27 Length of a cardboard box [cm]: 33

Volume of a cardboard box [m³]: 0.022275

ACCESSORIES:

KCPM-AX11 Blok styków pomocniczych do styczników

mocy miniaturowych - frontowe

24113 Blok styków pomocniczych do styczników mocy miniaturowych - frontowe KCPM-AX22





We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

