


## 32581 KMB6-B50/2

Miniature circuit breaker, 2P

5905339325815



Circuit breaker with overcurrent protection is used to protect cables against overloads and short circuits in installations and devices.

### GENERAL DATA:

**Place of assembly:** na szynę TH35

**Norm:** PN-EN 60898-1

**Length [mm]:** 76

**Width [mm]:** 35

**Height [mm]:** 82

### TECHNICAL DATA:

**Rated voltage [V]:** 230 AC

**Rated current [A]:** 50

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** 5÷40

**Range of sections of wires used [mm<sup>2</sup>]:** 1÷25

**Release characteristics:** B

**Energy-limit class:** 3

**Number of modules:** 2

**Rated short-circuit current [A]:** 6000

**IP class:** 20

**Rated insulation voltage UI [V]:** 500

**Number of poles:** 2

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 6

**Number of units in the secondary packaging:** 6

**Number of units in the packaging:** 60

**Net unit weight [g]:** 202

**Grammage [g]:** 218.33

**Length of a unit pack [cm]:** 4

**Width of a unit pack [cm]:** 7.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 13.0998

**Width of a cardboard box [cm]:** 25

**Height of a cardboard box [cm]:** 19.5

**Length of a cardboard box [cm]:** 45

**Volume of a cardboard box [m<sup>3</sup>]:** 0.021938