IDEAL TS
by **Kanlux**

32657 KP-DB-I-MS-624

Metal distribution board

5905339326577

CE | EHC | UK CA | (symbol)

GENERAL DATA:

Colour: white
Door colour: white
Place of assembly: wall mounted
Norm: PN-EN 62208
Length [mm]: 595
Width [mm]: 140
Height [mm]: 982

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC
Rated frequency [Hz]: 50
Class of protection against electric shock: I
Material: iron
Number of modules: 6x24P
IP class: 30
number of rows: 6

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 1
Number of units in the secondary packaging: 1
Number of units in the packaging: 1
Net unit weight [g]: 14300
Grammage [g]: 15700
Length of a unit pack [cm]: 99.5
Width of a unit pack [cm]: 61.5
Height of a unit pack [cm]: 15.5
Weight of a cardboard box [kg]: 15.7
Width of a cardboard box [cm]: 61.5
Height of a cardboard box [cm]: 15.5
Length of a cardboard box [cm]: 99.5
Volume of a cardboard box [m³]: 0.094848

Date of issue: 02.11.2023, 11:47
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN

IDEAL TS
by **Kanlux**

32657   KP-DB-I-MS-624

Metal distribution board

982
595
140

EN