


38542 KRD10-4/25/100-B

Residual-current circuit breaker, 4P

5905339385420



GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1

Length [mm]: 73

Width [mm]: 72

Height [mm]: 86.7

TECHNICAL DATA:

Rated voltage [V]: 400 AC

Rated current [A]: 25

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: do 35

Residual-current protection type: B

Number of modules: 4

Differential-rated current [mA]: 100

IP class: 20

Rated activation capacity[A]: 10000

Rated insulation voltage UI [V]: 400

Number of poles: 4

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 3

Number of units in the secondary packaging: 3

Number of units in the packaging: 30

Net unit weight [g]: 402

Grammage [g]: 461.33

Gross unit weight [g]: 424

Length of a unit pack [cm]: 8

Width of a unit pack [cm]: 9

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 13.8399

Width of a cardboard box [cm]: 27

Height of a cardboard box [cm]: 19

Length of a cardboard box [cm]: 49.5

38542 KRD10-4/25/100-B

Residual-current circuit breaker, 4P

| Volume of a cardboard box [m³] : 0.025394