


38741 KRD10-4/40/30-AC

Residual-current circuit breaker, 4P

5905339387417



GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1

Length [mm]: 75

Width [mm]: 72

Height [mm]: 82

TECHNICAL DATA:

Rated voltage [V]: 400 AC

Rated current [A]: 40

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: do 35

Residual-current protection type: AC

Number of modules: 4

Differential-rated current [mA]: 30

IP class: 20

Rated activation capacity[A]: 10000

Rated insulation voltage UI [V]: 400

Number of poles: 4

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 30

Number of units in the secondary packaging: 1

Number of units in the packaging: 30

Net unit weight [g]: 352

Grammage [g]: 391.33

Gross unit weight [g]: 378

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 7.5

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 11.7399

Width of a cardboard box [cm]: 27.5

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm]: 47

38741 KRD10-4/40/30-AC

Residual-current circuit breaker, 4P

| Volume of a cardboard box [m³] : 0.023911