


38746 KRD10-4/63/30-A

Residual-current circuit breaker, 4P
5905339387462



GENERAL DATA:

Colour: white
Place of assembly: na szynę TH35
Norm: PN-EN 61008-1
Length [mm]: 75
Width [mm]: 72
Height [mm]: 82

TECHNICAL DATA:

Rated voltage [V]: 400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Ambient temperature range to which the product can be exposed: -25÷40
Range of sections of wires used [mm²]: do 35
Residual-current protection type: A
Number of modules: 4
Differential-rated current [mA]: 30
IP class: 20
Rated activation capacity[A]: 10000
Rated insulation voltage UI [V]: 400
Number of poles: 4

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 30
Number of units in the secondary packaging: 1
Number of units in the packaging: 30
Net unit weight [g]: 364
Grammage [g]: 406.67
Gross unit weight [g]: 390
Length of a unit pack [cm]: 9
Width of a unit pack [cm]: 8
Height of a unit pack [cm]: 8
Weight of a cardboard box [kg]: 12.2001
Width of a cardboard box [cm]: 27.5
Height of a cardboard box [cm]: 18
Length of a cardboard box [cm]: 47

38746 KRD10-4/63/30-A

Residual-current circuit breaker, 4P

| **Volume of a cardboard box [m³] :** 0.023265